

LY-1200HS LY-1600HS

FULLY AUTOMATIC HOT SLITTING & SEALING MACHINE.
(THIS MACHINE CONVERTS FROM SINGLE PE SHEET TO TUBULAR FILM)



Features

- Servo motor for rewinding unit.
- Line position control.
- Auto-tension control for unwinding stand.
- Auto-tension control for rewinding stand.
- Edge trimming and waste collecting unit.
- Air shaft for rewinding and unwinding
- Digital line speed display
- Digital meter-counter display

Specification

Model	Max.Film Width	Film Thickness	Max Production	Material	Max. Reel Dia.	Max. Reel Weight
LY-1200HS	1200 mm	0.03-0.1 mm	up to 180 M/per min	LLDPE, LDPE, HDPE, CPP	700 mm	200kgs
LY-1600HS	1600 mm	0.03-0.1 mm	up to 180 M/per min	LLDPE, LDPE, HDPE, CPP	700 mm	200kgs

Model	Power Required	Machine Dimensions			Machine weight (KG)
		L (M)	W (M)	H (M)	
LY-1200HS	7 kw	4.5	2.5	1.6	1300
LY-1600HS	7 kw	5.0	2.65	1.6	1500

Notes : due to continual research and improvement, mechanical specifications are subject to further revision without prior notice.